

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** ZRC and Galviline Cold Galvanizing Compounds - Aerosol

**Other means of identification**

**Product code** 10000, 20010

**Recommended use** Corrosion protection of iron and steel.

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Supplier/Manufacturer** ZRC Worldwide  
**Address** 145 Enterprise Drive, Marshfield, MA 02050  
**Telephone** 781-319-0400  
**Emergency telephone (CHEMTREC)** 703-527-3887 CCN15781  
**Email** info@zrcworldwide.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
<b>Health hazards</b>	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye/face protection.

**Response** If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

## 3. Composition/information on ingredients

**Mixtures**

Chemical name	CAS number	%
Zinc	7440-66-6	40 - < 50
Acetone	67-64-1	20 - < 30
Propane	74-98-6	5 - 15
Methyl Ethyl Ketone	78-93-3	5 - 10
Stoddard solvent	8052-41-3	5 - < 10
N-Butane	106-97-8	3 - 8
Zinc oxide	1314-13-2	1 - < 3
Other components below reportable levels		3 - < 5

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth. Get medical attention if any discomfort continues.
<b>Most important symptoms/effects, acute and delayed</b>	Causes serious eye irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Dry chemicals. Foam. Class B fire extinguisher.
<b>Unsuitable extinguishing media</b>	Water. Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Water runoff can cause environmental damage.
<b>General fire hazards</b>	Extremely flammable aerosol.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protective equipment. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Collect spillage. Scoop up used absorbent into drums or other appropriate container. Prevent product from entering drains. For waste disposal, see Section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not taste or swallow. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

### Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
Methyl Ethyl Ketone (CAS 78-93-3)	PEL	590 mg/m3	
Propane (CAS 74-98-6)	PEL	200 ppm 1800 mg/m3 1000 ppm	
Stoddard solvent (CAS 8052-41-3)	PEL	2900 mg/m3 500 ppm	
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3 5 mg/m3 15 mg/m3	Respirable fraction. Fume. Total dust.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL TWA	750 ppm 500 ppm	
Methyl Ethyl Ketone (CAS 78-93-3)	STEL TWA	300 ppm 200 ppm	
N-Butane (CAS 106-97-8)	STEL	1000 ppm	
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Zinc oxide (CAS 1314-13-2)	STEL TWA	10 mg/m3 2 mg/m3	Respirable fraction. Respirable fraction.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm	
Methyl Ethyl Ketone (CAS 78-93-3)	STEL TWA	885 mg/m3 300 ppm 590 mg/m3 200 ppm	
N-Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	
Stoddard solvent (CAS 8052-41-3)	Ceiling TWA	1800 mg/m3 350 mg/m3	
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.

## US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
	STEL	10 mg/m <sup>3</sup>	Fume.
	TWA	5 mg/m <sup>3</sup>	Fume.
		5 mg/m <sup>3</sup>	Dust.

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Methyl Ethyl Ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*

\* - For sampling details, please see the source document.

### Exposure guidelines

#### US - California OELs: Skin designation

Methyl Ethyl Ketone (CAS 78-93-3)

Can be absorbed through the skin.

#### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Avoid contact with eyes. Wear safety glasses with side shields (or goggles). Eye wash fountain and emergency showers are recommended.

#### Skin protection

##### Hand protection

For prolonged or repeated skin contact use suitable protective gloves. Neoprene gloves are recommended.

##### Other

Wear appropriate chemical resistant clothing.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

#### General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

Appearance	Gray liquid.
Physical state	Gas.
Form	Aerosol. Aerosol- Pressurized Liquid.
Color	Gray.
Odor	Hydrocarbon.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	395.6 °F (202 °C)
Flash point	< 19.4 °F (< -7.0 °C) Tag Open Cup
Evaporation rate	> 1 BuAc (n-Butyl acetate=1)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1
Flammability limit - upper (%)	12.8
Explosive limit - lower (%)	Not available.

<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	50 mm Hg (21°C / 70°F)
<b>Vapor density</b>	> 1 (24°C / 77°F)
<b>Relative density</b>	1.2
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Slightly soluble in water.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Bulk density</b>	10.01 lb/gal
<b>VOC (Weight %)</b>	< 30 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point.
<b>Incompatible materials</b>	Avoid contact with acids and alkalis. Strong oxidizing agents. Water.
<b>Hazardous decomposition products</b>	Zinc oxides. CO, CO2, Various hydrocarbon gases. Contact with acids will release flammable hydrogen gas.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Vapors may cause drowsiness and dizziness.
<b>Skin contact</b>	Prolonged or repeated contact may dry skin and cause irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** Causes serious eye irritation. Symptoms include itching, burning, redness, and tearing of eyes. Vapors may cause drowsiness and dizziness.

### Information on toxicological effects

**Acute toxicity** May cause discomfort if swallowed.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	20 ml/kg
<i>Inhalation</i>		
LC50	Rat	50 mg/l, 8 Hours
<i>Oral</i>		
LD50	Rat	5800 mg/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	1355 mg/l

Components	Species	Test Results
Stoddard solvent (CAS 8052-41-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Zinc (CAS 7440-66-6)		
<b>Acute</b>		
<i>Oral</i>		
LD50	Rat	630 mg/kg
<b>Skin corrosion/irritation</b>	Not classified.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not classified.	
<b>Skin sensitization</b>	Not classified.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Not classifiable as to carcinogenicity to humans.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Not available.		
<b>NTP Report on Carcinogens</b>		
Not available.		
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>		
Not listed.		
<b>Reproductive toxicity</b>	Not classified.	
<b>Specific target organ toxicity - single exposure</b>	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	Not classified.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	

## 12. Ecological information

<b>Ecotoxicity</b>	Very toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.		
<b>Components</b>	<b>Species</b>	<b>Test Results</b>	
Acetone (CAS 67-64-1)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	> 100 mg/l, 96 hours
Zinc (CAS 7440-66-6)			
<b>Aquatic</b>			
Crustacea	LC50	Daphnia magna	0.068 mg/l, 48 hours
Zinc oxide (CAS 1314-13-2)			
<b>Aquatic</b>			
Crustacea	LC50	Water flea ( <i>Daphnia magna</i> )	0.098 mg/l, 48 Hours
<b>Persistence and degradability</b>	No data is available on the degradability of this product.		
<b>Bioaccumulative potential</b>	No data available for this product.		
<b>Partition coefficient n-octanol / water (log Kow)</b>			
Acetone (CAS 67-64-1)	-0.24		

**Partition coefficient n-octanol / water (log Kow)**

Methyl Ethyl Ketone (CAS 78-93-3)	0.29
N-Butane (CAS 106-97-8)	2.89
Propane (CAS 74-98-6)	2.36
Stoddard solvent (CAS 8052-41-3)	3.16 - 7.15

**Mobility in soil** Not available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F  
D003: Waste Reactive material

**Waste from residues / unused products** Dispose of in accordance with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

**14. Transport information****DOT**

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** Yes  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IATA**

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards** Yes  
**ERG Code** 10L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** Yes  
**EmS** Not available.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**General information** Limited Quantity exemption may apply.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	LISTED
Methyl Ethyl Ketone (CAS 78-93-3)	LISTED
N-Butane (CAS 106-97-8)	LISTED
Propane (CAS 74-98-6)	LISTED
Zinc (CAS 7440-66-6)	LISTED
Zinc oxide (CAS 1314-13-2)	LISTED

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Zinc	7440-66-6	40 - < 50
Zinc oxide	1314-13-2	1 - < 3

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)	6532
Methyl Ethyl Ketone (CAS 78-93-3)	6714

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35 %WV
Methyl Ethyl Ketone (CAS 78-93-3)	35 %WV

#### DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
Methyl Ethyl Ketone (CAS 78-93-3)	6714

**US state regulations** This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

#### US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)  
Methyl Ethyl Ketone (CAS 78-93-3)  
N-Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)  
Stoddard solvent (CAS 8052-41-3)  
Zinc (CAS 7440-66-6)  
Zinc oxide (CAS 1314-13-2)

#### US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)



Methyl Ethyl Ketone (CAS 78-93-3)  
N-Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)  
Stoddard solvent (CAS 8052-41-3)  
Zinc (CAS 7440-66-6)  
Zinc oxide (CAS 1314-13-2)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)  
Methyl Ethyl Ketone (CAS 78-93-3)  
N-Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)  
Stoddard solvent (CAS 8052-41-3)  
Zinc (CAS 7440-66-6)  
Zinc oxide (CAS 1314-13-2)

#### US. Rhode Island RTK

Acetone (CAS 67-64-1)  
Methyl Ethyl Ketone (CAS 78-93-3)  
N-Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)  
Zinc (CAS 7440-66-6)  
Zinc oxide (CAS 1314-13-2)

#### US. California Proposition 65

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information, including date of preparation or last revision

Issue date 14-December-2013  
Revision date 17-January-2014  
Version # 03

#### NFPA ratings



#### List of abbreviations

#### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.